





中国认可 国际互认 检测 TESTING CNAS L0599

Page 1 of 10

Test Report SL52025269304801TX Date:June 15,2020

DONGGUAN SENGTOR PLASTICS PRODUCTS Co., LTD

NO.16 PUXIN COMMERCIAL STREET, SHIPAI TOWN, DONGGUAN, GUANGDONG, CN

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description : (A)Particle filtering half mask

Claimed : FFP2

SGS Internal Ref No. : GZHL2005018278MD

Style No. : 3199061 Sample Color : (A)White

Manufacturer : DONGGUAN SENGTOR PLASTICS PRODUCTS Co., LTD

Country of Destination : EUR
Country of Origin : China
Item No./Size : 3199061

Test Performed : Selected test(s) as requested by applicant

Sample Receiving Date : Jun 02, 2020

Testing Period : Jun 02, 2020 - Jun 15, 2020

Test Result(s) : Unless otherwise stated the results shown in this test report refer only to the


sample(s) tested, for further details, please refer to the following page(s).

# **Conclusion:**

Sample No.	Recommendation Level	
(A)	FFP2 NR	

Signed for and on behalf of

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd Testing Center





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms



SL52025269304801TX

Date:June 15,2020

Page 2 of 10

Test Result

#### Personal Protective Equipment - Respiratory Protective Devices- Filtering Half Masks to Protect against Particles- Requirements, Testing, Marking

EN 149:2001+A1:2009

#### Clause 7.4 Packaging

(EN 149:2001+A1:2009 Clause 8.2)

Test Requirement	Results	Comment
Particle filtering half masks shall be offered for sale packaged in such a way that they are protected against mechanical damage and contamination before use.	Comply	Pass

#### Clause 7.5 Material

(EN 149:2001+A1:2009, Clause 8.2 & 8.3.1 & 8.3.2)

Test Requirement	Results	Comment
Materials used shall be suitable to withstand handling and wear over the period for which the particle filtering half mask is designed to be used.	Comply	
After undergoing the conditioning described in 8.3.1 none of the particle filtering half masks shall have suffered mechanical failure of the facepiece or straps.	Comply	Pass
When conditioned in accordance with 8.3.1 and 8.3.2 the particle filtering half mask shall not collapse.	Comply	
Any material from the filter media released by the air flow through the filter shall not constitute a hazard or nuisance for the wearer.	Comply	

# Clause 7.6 Cleaning and Disinfecting

(EN 149:2001+A1:2009, Clause 8.4 & 8.5 & 8.11)

Test Requirement	Results	Comment
If the particle filtering half mask is designed to be re-usable, the materials used shall withstand the cleaning and disinfecting agents and procedures to be specified by the manufacturer.  With reference to 7.9.2, after cleaning and disinfecting the re-usable particle filtering half mask shall satisfy the penetration requirement of the relevant class.	Not applicable (Not designed to be re-usable)	N.A.

### Clause 7.7 Practical Performance

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The particle filtering half mask shall undergo practical performance test under realistic conditions. These general tests serve the purpose checking the equipment for imperfections that cannot be determined by the tests described elsewhere in this standard.	of No imperfections	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms

3<sup>rd</sup>Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52025269304801TX

Date:June 15,2020

Page 3 of 10

# **Clause 7.8 Finish of Parts**

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
Parts of the device likely to come into contact with the wearer shall have no	Comply	Pass
sharp edges or burrs.	Comply	F 455

# Clause 7.9.1 Total Inward Leakage

(EN 149:2001+A1:2009, Clause 8.5)

Test Requirement	Results	Comment
The total inward leakage consists of three components: face seal leakage, exhalation value leakage(if exhalation value fitted) and filter penetration. For particle filtering half masks fitted in accordance with the manufacturer's information, at least 46 out of the 50 individual exercise results (i.e. 10 subjects x 5 exercises) for total inward leakage shall be not greater than: 25% for FFP1, 11% for FFP2, 5% for FFP3  and, in addition, at least 8 out of the 10 individual wearer arithmetic means for the total inward leakage shall be not greater than: 22% for FFP1, 8% for FFP2, 2% for FFP3	Detail refer to Appendix 1	Pass

# **Appendix 1: Summarization of Test Data**

Inward Leakage Test Data

Subject	Sample	Condition	Walk(%)	Head	Head	Talk(%)	Walk(%)	Mean(%)
	No.		, ,	Side/side(%)	up/down(%)	, ,	, ,	` ,
Zhou	1	A.R.	5.85	6.94	6.73	4.55	6.87	6.19
Luo	2	A.R.	8.14	6.59	8.21	6.66	7.15	7.35
Lu	3	A.R.	6.20	6.82	6.34	7.38	4.87	6.32
Wang	4	A.R.	5.29	4.48	5.88	4.85	5.06	5.11
Bao	5	A.R.	8.07	7.87	6.44	6.84	7.98	7.44
Ding	6	T.C.	4.26	6.65	6.18	4.76	4.79	5.33
Li	7	T.C.	7.64	7.73	8.58	6.95	7.13	7.61
Chen	8	T.C.	6.27	6.62	4.93	4.50	5.25	5.51
Song	9	T.C.	6.18	6.86	7.06	7.02	6.45	6.71
Ye	10	T.C.	7.96	7.19	7.28	8.93	8.02	7.88

#### Facial Dimension(mm)

Subject	Face length	Face Width	Face Depth	Mouth Width
Chen	125	150	120	58
Lu	115	132	107	48
Zhou	115	135	106	52
Li	125	130	107	46
Luo	125	136	100	43
Zheng	128	140	112	55
Wang	120	147	103	48
Song	120	140	100	50
Bao	130	134	104	50



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms

3<sup>rd</sup>Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮編: 200233 t (86-21) 61402666 f (86-21) 64958763 t (86-21) 61402666

f (86-21) 64958763



Test Rep	ort SL5202	5269304801TX	Date:June 15,2020	Page 4 of 10
Ding	134	150	110	52
Liu	120	135	117	50
Ye	126	137	105	52

# Clause 7.9.2 Penetration of Filter Material

(EN 149:2001+A1:2009, Clause 8.11 & EN 13274-7:2019)

	Test Requirement	Results	Comment		
The penetration	of the filter of the particle fil	ltering half mask shall m	eet the		
requirements of	the following table.	_			
Classification	Maximum penetration	on of test aerosol			
	Sodium chloride test 95	Paraffin oil test 95			
	l/min	l/min		Detail refer to	
	%	%		Appendix 2	Pass
	max.	max.			
FFP1	20	20			
FFP2	6	6			
FFP3	1	1			

# **Appendix 2: Summarization of Test Data**

### Penetration of filter material

Aerosol	Condition	Sample No.	Penetration (%)
		1	0.313
	As received	2	0.413
		3	0.217
		4	0.378
Sodium chloride test	Simulated wearing treatment	5	0.412
	_	6	0.370
	Mechanical strength +Temperature	7	1.279
		8	1.346
	conditioned	9	1.427
		10	0.668
	As received	11	0.448
		12	0.532
		13	0.564
Paraffin oil test	Simulated wearing treatment	14	0.487
	_	15	0.606
	Mark animal atmosphilib . Tanan anatoma	16	4.165
	Mechanical strength +Temperature	17	3.769
	conditioned	18	4.065
	Flow conditioning: Single fil	ter: 95.0 L/min	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms

3<sup>rd</sup>Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52025269304801TX

Date:June 15,2020

Page 5 of 10

### Clause 7.10 Compatibility with Skin

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
Materials that may come into contact with the wearer's skin shall not be known to be likely to cause irritation or any other adverse effect to health.	No irritation or any other adverse effect to health	Pass

#### Clause 7.11 Flammability

(EN 149:2001+A1:2009, Clause 8.6)

Test Requirement	Results	Comment
The material used shall not present a danger for the wearer and shall not be of highly flammable nature	Detail refer to	Pass
When tested, the particle filtering half mask shall not burn or not to continue to burn for more than 5 s after removal from the flame.	Appendix 3	1 433

### **Appendix 3: Summarization of Test Data**

#### **Flammability**

Condition	Sample No.	Result
	1	NIL
As received	2	NIL
	3	NIL
Temperature conditioned	4	NIL

# Clause 7.12 Carbon Dioxide Content of The Inhalation Air

(EN 149:2001+A1:2009, Clause 8.7)

Test Requirement	Results	Comment
The carbon dioxide content of the inhalation air (dead space) shall not	Detail refer to	Pass
exceed an average of 1,0 % (by volume)	Appendix 4	F 455

#### **Appendix 4: Summarization of Test Data**

Carbon Dioxide Content of The Inhalation Air

Condition	Sample No.	Result(%)				
	1	0.4738				
As received	2	0.4742	Mean value:0.47			
	3	0.4730				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms

3<sup>rd</sup>Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 f (86-21) 64958763 t (86-21) 61402666

f (86-21) 64958763



SL52025269304801TX

Date:June 15,2020

Page 6 of 10

# **Clause 7.13 Head Harness**

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
The head harness shall be designed so that the particle filtering half mask can be donned and removed easily.	Comply	
The head harness shall be adjustable or self-adjusting and shall be sufficiently robust to hold the particle filtering half mask firmly in position and be capable of maintaining total inward leakage requirements for the device.	Comply	Pass

#### Clause 7.14 Field of Vision

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The field of vision is acceptable if determined so in practical performance	Comply	Pass
tests.		rass

# Clause 7.15 Exhalation Valve(s)

(EN 149:2001+A1:2009, Clause 8.2 & 8.9.1 & 8.3.4 & 8.8)

Test Requirement	Results	Comment
(a) A particle filtering half mask may have one or more exhalation valve(s), which shall function correctly in all orientations.	Not applicable due to No exhalation valve	
(b) If an exhalation valve is provided it shall be protected against or be resistant to dirt and mechanical damage and may be shrouded or may include any other device that may be necessary for the particle filtering half mask to comply with 7.9.	Not applicable due to No exhalation valve	N.A.
(c) Exhalation valve(s), if fitted, shall continue to operate correctly after a continuous exhalation flow of 300 l/min over a period of 30 s.	Not applicable due to No exhalation valve	
(d) When the exhalation valve housing is attached to the faceblank, it shall withstand axially a tensile force of 10N applied for 10 s.	Not applicable due to No exhalation valve	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms

3<sup>rd</sup>Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮編: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52025269304801TX

Date:June 15,2020

Page 7 of 10

### Clause 7.16 Breathing Resistance

(EN 149:2001+A1:2009, Clause 8.9)

	Tes	Results	Comment			
The penetration requirements of						
Classification	Classification Maximum permitted resistance (mbar)					
	Inhalation Exhalation				Detail refer to	Pass
	30 l/min	95 I/min	160 l/min		Appendix 5	
FFP1	0.6	2.1	3.0			
FFP2	0.7	2.4	3.0			
FFP3	1.0	3.0	3.0			

## **Appendix 5: Summarization of Test Data**

# Breathing resistance (mbar)

	[]	/:-\			1					2					3		
	Flow rate(l/	min)	Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е
As received	Inhalation	30	0.2	0.2	0.3	0.2	0.3	0.2	0.3	0.2	0.3	0.2	0.3	0.2	0.3	0.2	0.3
	IIIIaiation	95	0.7	0.6	0.7	0.8	0.6	0.7	8.0	0.7	0.6	0.7	0.8	0.6	0.8	0.7	8.0
	Exhalation	160	1.9	1.9	1.8	1.9	2.0	1.9	1.8	2.0	1.8	2.0	1.9	1.8	2.0	1.9	1.8
	[]noto/	/:\			4					5				6 B C D E			
Simulated	Flow rate(I/	min)	Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е
wearing	Inhalation —	30	0.3	0.4	0.3	0.4	0.3	0.4	0.3	0.3	0.4	0.3	0.4	0.3	0.4	0.3	0.3
treatment		95	0.7	0.8	0.9	0.8	0.9	0.7	0.7	0.9	0.8	0.8	0.9	0.7	0.8	0.9	0.7
	Exhalation	160	1.9	2.0	2.1	1.9	2.1	2.1	1.9	2.1	2.0	1.9	2.0	1.9	2.1	2.0	1.9
	[]noto/	/:\			7				8 9								
	Flow rate(I/	min)	Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е
Temperature	Inhalation	30	0.2	0.2	0.3	0.2	0.2	0.3	0.2	0.3	0.2	0.3	0.2	0.2	0.3	0.2	0.2
conditioned	IIIIaialiOII	95	0.7	0.6	0.7	0.8	0.6	0.7	0.7	0.6	0.8	0.7	0.8	0.6	0.7	0.6	0.7
	Exhalation	160	2.0	1.9	2.1	1.9	2.1	2.0	2.1	1.9	2.0	1.9	2.1	2.0	1.9	2.0	2.1

A: facing directly ahead; B: facing vertically upwards; C: facing vertically downwards; D: lying on the left side; E: lying on the right side



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms

3<sup>rd</sup>Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国·上海·徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52025269304801TX

Date:June 15,2020

Page 8 of 10

### Clause 7.17 Clogging

(EN 149:2001+A1:2009, Clause 8.9 & 8.10)

	Test Requirement	Results	Comment
Valved particle fill After clogging the FFP1: 4 mbar, FI The exhalation re flow.  Valveless particle After clogging the	eathing resistance tering half masks: e inhalation resistances shall not FP2: 5 mbar, FFP3: 7 mbar at 95 esistance shall not exceed 3 mb e filtering half masks: e inhalation and exhalation resis FP2: 4 mbar, FFP3: 5 mbar at 95	Optional for single shift device only	N.A.
All types (valved	enetration of filter material I and valveless) of particle filter g requirement shall also meet th  Maximum penetration Sodium chloride test 95 l/min % max. 20 6 1	Optional for single shift device only	N.A.

#### **Clause 7.18 Demountable Parts**

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
All demountable parts (if fitted) shall be readily connected and secured, where possible by hand	Comply	Pass

Test	Uncertainty
Total inward leakage	3.4%
Penetration of filter material	4.8%
Carbon dioxide content of the inhalation air	3.9%
Breathing resistance (30L/min)	5.9%
Breathing resistance (95L/min)	4.9%
Breathing resistance (160L/min)	4.3%



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms

3<sup>st</sup>Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐江区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 f (86-21) 64958763 t (86-21) 61402666 f (86-21) 64958763



SL52025269304801TX

Date:June 15,2020

Page 9 of 10







Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms

3<sup>rd</sup>Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52025269304801TX

Date:June 15,2020

Page 10 of 10



\*\*\*End of Report\*\*\*



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms